



Setting standards in laundry finish and efficiency

11



The new high-performance flatwork ironers Convincing performance, laundry finish and operation



Endowed with innovative product features and built using high-quality components, the new high-performance flatwork ironers from Miele Professional set new standards in terms of performance, laundry finish and operability – making for ideal working conditions in both OPLs and contract laundries.

Forever better

Miele is the epitome of quality. For more than 111 years, Miele has subscribed to a corporate philosophy of being 'forever better'. A quality promise that stands for perfect systematic solutions in laundry care. All Miele products are designed and manufactured to exacting quality standards. Miele's new high-performance flatwork ironers are a prime example of the consistent use of innovative technology and clearly underline Miele's role as technology leader.

Setting new standards in OPLs and contract laundries

Meeting the highest of demands regarding laundry finish combined with high throughput requires on the one hand a well-rehearsed team and, on the other, a machine that both performs to perfection and is simple to use. With their perfectly matching high-quality components, the new high-performance flatwork ironers from the PM 16 and PM 18 generation from Miele Professional offer the wherewithal to produce unbeatable results.

Highest performance

The new high-performance flatwork ironers are available in various sizes and with a variety of heating systems:

Roller length: 2.10 m to 3.50 m
Roller diameter: 60 or 80 cm
Heating: Gas, electric or steam

With a roller speed of up to 16 m per minute, it is possible to cope with around 1.6 tonnes* of laundry in a single shift. This allows huge mountains of laundry to be processed in the shortest of times. And a special heat-retaining cover ensures that no energy is wasted, reducing costs and protecting the roller and the trough against any ingress of dirt and dust.

*Throughput is dependent on the net roller length and the roller diameter.

Perfect laundry finish

Perfectly laundered flatwork makes for good first impressions and raises the reputation of a laundry. With their high and uniform contact pressure in combination with a solid, rugged trough and a large contact angle, the new high-performance flatwork ironers are veritable powerhouses ensuring a perfect laundry finish.

Honeycomb perforations allow room air to cool textiles on the patented EasyFold outfeed table, nicely fixing the laundry finish in place.


Perfect, simple operation

In terms of operability, the new ironers support optimum working patterns thanks to ergonomic operation and flexible controls with a large touch screen.

As different types of laundry and varying residual moisture levels require their own specific parameters, operators can chose from standard programmes or simply compile and save their own to suit the needs of particular textiles or clients. And, to simplify work even further, these settings can be called up at any time with ease.

The benefits

- High throughput
- Superb laundry finish
- · Highest quality
- Textile- and customer-specific programmes
- Ergonomic working conditions
- Simple operation



Wide range of features Glossary

Features

A whole host of product features from the Miele portfolio ensure excellent ergonomics and productivity, a superb laundry finish, workplace safety and cost-effectiveness:

Standard features

Feature	User benefit
Round spring padding	Durable, supple and long-lasting roller padding with good spring action to compensate for variations in the thickness of flatwork.
Polyester needle felt	Good no-jerk traction.
Infeed table with belt feed	Simple introduction of textiles.
FlexControl footswitch	Helps ensure that items are smooth when fed in. Belts and roller stop immediately when the footswitch is operated. The footswitch can be relocated for greatest convenience.
EasyFold outfeed table	Miele patented outfeed table with honeycomb relief design: Honeycomb perforations allow room air to cool textiles while still on the outfeed table. The gentle current of air fixes the laundry finish in place.
Finger guard	The finger guard is activated immediately whenever fingers get too close to the roller when introducing items of laundry. Feed belts and the roller stop at once and the roller is raised safely out of the trough.

Special features

Feature	User benefit			
Fishscale padding	Durable roller padding, particularly suitable for high-quality linen as this type of padding guarantees extremely even contact pressure.			
ARAMID needle felt cloth	This covercloth material is prized for its extreme durability.			
Heat-retaining cover	Prevents excessive heat losses to atmosphere. Heat energy stays where it is needed. This accessory also off the secondary benefit of protecting both trough and roller against any ingress of dust.			
Return feed	Allows laundry to be introduced and removed from the front of the machine. Easily converted from through-fee to return feed (without having to remove the heat-retaining cover).			
Laundry rail	For small items of laundry – simplifies pre-sorting and the introduction of items. Hinged to allow longer items to drape in front of the machine.			
Hygiene floorplate	Prevents larger items of laundry from trailing on the floor.			
Second FlexControl footswitch	Makes the footswitch more accessible when there are several persons operating a machine.			
'Plus' infeed table	Deeper, height-adjustable infeed table with suction through perforated feed belts: Adapts perfectly to operating staff, simplifies work procedures and improves workplace ergonomics.			
Laser infeed guide	Projects a line denoting the leading edge of items onto infeed table. Simplifies introduction of items and optimises results by ensuring parallel infeed.			
Multi-lane remoisturising of flatwork	Simplifies the ironing of overly dry textiles. 1, 2 or 3 lanes selectable.			
Second contact pressure	Improved finish and increased laundry throughput when ironing multi-ply or thicker textiles. Manually activated. The alternative contact pressure can be programmed into individual programmes.			
Timer	Allows times to be recorded for individual orders or batches. Simplifies processing and invoicing.			
Extended ironer speed range	More finely adjustable, faster ironer speed: 3 – 14 m/min. on 60 cm roller diameter or 4 – 16 m/min. on 80 cm roller diameter			
Auto heat-up on steam-heated versions	Staged control of steam valve at machine switch-on (only on steam-heated version).			
Infinitely adjustable steam control including auto heat-up	Temperature controls as per electric and steam-heated versions, incl. auto heat-up (only on steam-heated version).			
Internal compressed air generation (in absence of on-site supply)	A compressor is provided if there is no compressed air generating equipment on site.			
Trough cleaning and waxing prompt	Maintains the quality of finish by ensuring that the trough is cleaned and waxed regularly by issuing a display prompt which must be acknowledged by operating staff.			
Accessories for cleaning and waxing the trough	Cleaning cloth, waxing cloth and ironer wax – ensures long-lasting care of trough.			

Technical data

Flatwork ironers	PM 1621	PM 1625	PM 1630	PM 1635
Roller length [mm]	2100	2500	3000	3500
Roller diameter [mm]	585	585	585	585
Heating	EL/G	EL/G/S	EL/G/S	EL/G/S
Electrical connection				
Mains voltage 3N AC 400 V 50 Hz	•	•	•	•
Total rated load (electric version) [kW]	63.7	63.7	63.7	63.7
Total rated load (gas version) [kW]	3.9	3.9	3.9	3.9
Total rated load (steam version) [kW]	-	2.2	2.2	2.2
Heater rating (electric version) [kW]	60	60	60	60
Heater rating (gas version) [max. kW]	75	75	75	75
Heater rating (steam version) [kW]	-	60	60	60
Performance*				
Maximum throughput (electric/gas/steam) [kg/h]	115/115/-	130/130/135	145/145/165	160/160/190
Dimensions, weight				
Ext. dimensions H/W/D [mm]	1970/3290/1840	1970/3690/1840	1970/4190/1840	1970/4690/1840
Weight (electric/gas/steam) [kg]	2260/2370/-	2420/2530/2370	2620/2730/2590	2810/2930/2810
Flatwork ironers		PM 1825	PM 1830	PM 1835
Roller length [mm]		2500	3000	3500
Roller diameter [mm]		790	790	790
Heating		EL/G/S	EL/G/S	G/S
Electrical connection				
Mains voltage 3N AC 400 V 50 Hz		•	•	•
Total rated load (electric version) [kW]		84.6	84.6	-
Total rated load (gas version) [kW]		4.8	4.8	4.8
Total rated load (steam version) [kW]		3.1	3.1	3.1
Heater rating (electric version) [kW]		80	80	-
Heater rating (gas version) [max. kW]		100	100	100
Heater rating (steam version) [kW]		80	80	80
Performance*				
Maximum throughput (electric/gas/steam) [kg/h]		165/165/165	200/200/200	-/235/235
Dimensions, weight				
Ext. dimensions H/W/D [mm]		1970/3690/2044	1970/4190/2044	1970/4690/2044
Weight (electric/gas/steam) [kg]		2860/2970/3050	3110/3230/3360	-/3490/3660
• = standard, – = not available				
- otanidara, - not avallable				

EL = Electric, G = Gas, S = Steam, *Throughput according to DIN 11902, at 50% residual moisture

Feed belts



Finger guard



Heat-retaining cover (open)





Miele & Cie. KG Miele Deutschland Carl-Miele-Straße 29, 33332 Gütersloh P.O. Box, 33325 Gütersloh

www.miele-professional.de info@miele.de

Miele worldwide:

AUSTRALIA Miele Australia Pty. Ltd. 1 Gilbert Park Drive Knoxfield, VIC, 3180 Tel. +613 97647130 Telefax +613 97647149

AUSTRIA Miele Gesellschaft mbH. Mielestraße 1 5071 Wals/Salzburg Tel. +43 50 800-81 481 Telefax +43 50 800-81 429

BELGIUM N.V. Miele S.A. z.5 Mollem 480 Hof te Bollebeeklaan 9 1730 Mollem Tel. +32 2451 14 11 Telefax +32 2451 14 14

CANADA Miele Limited 161 Four Valley Drive Vaughan, ON L4K 4V8 Tel. +1 905 660-9936 Telefax +1 904 532-2290

CHILE Miele Ltda. Nueva Costanera 4055 Vitacura Santiago de Chile Tel. +56 2 95700-00 Telefax +56 2 95700-79

CHINA Miele Beijing Rep. Office 3W Suite 512, Oriental Plaza, 1 East Chang An Avenue Dong Cheng District Beijing 100738, P.R. China Tel. +86 10 85151919 Telefax +86 10 85181797

Miele (Shanghai) Trading Ltd. 1-3 Floor, No. 82 Shi Men Yi Road, Jing'An District 200040 Shanghai, China Tel. +86 21 61573500 Telefax +86 21 61573511

CROATIA Miele trgovina i servis d.o.o. Buzinski prilaz 32 10000 Zagreb Tel. +385/1/66 89 000 Telefax +385/1/66 89 090

CZECH REPUBLIC Miele spol. s.r.o. Holandská 4 63900 Brno Tel. +420 5 4 35 53-1 11 Telefax +420 5 4 35 53-1 19

DENMARK Miele A/S 2600 Glostrup, Erhvervsvej 2 Tel. +4543271100 Tel. Salg/Professional +4543271500 Tel. Jylland +4597127066 Telefax hovednr. +4543271109 Telefax Salg/Professional +4543271509 ESTONIA Miele OÜ Tornimäe 5 10145 Tallinn Tel. +372 6 55 68 11

FINLAND Miele Oy Porttikaari 6 01200 Vantaa Tel. +3589 87 59 70 Telefax +3589 87 59 72 99

FRANCE Miele S.A.S. 9 avenue Albert Einstein 93151-Le Blanc-Mesnil (Paris) Tel. +33(0)1/49 39 34 44 Telefax +33(0)1/49 39 44 38

GERMANY Miele & Cie. KG Carl-Miele-Straße 29 33332 Gütersloh Tel. 0 180 220 21 21 (6 ct)* Telefax 0 800 225 57 55 *Only in Germany

GREAT BRITAIN
Miele Co. Ltd.
Fairacres
Marcham Road, Abingdon
Oxon OX14 1TW
Tel. 0845 330 3618
Telefax 01235 405636

GREECE Miele Hellas E.P.E. Mesogion 257 154 51 N. Psychiko-Athens Tel. national 01/10 6 79 44 44 international 00 30/2/10 6 79 44 44 Telefax 01/10 6 79 42 09 international 00 30/2/10 6 79 42 09

HUNGARY Miele Kft. Alsó Törökvész út 2. 1022 Budapest Tel. +36 1 8806-400 Telefax +36 1 8006-402

HONG KONG Miele (Hong Kong) Ltd. 41/F - 4101, Manhattan Place 23 Wang Tai Road, Kowloon Bay Tel. +852/2610 1331 Telefax +852/2610 1013

INDIA Miele India Pvt. Ltd. Ground Floor, Copia Corporate Suites, Plot No. 9, Jasola, New Delhi – 110025 Tel. +91 (0)11 469000-00 Telefax +91 (0)11 469000-01

IRELAND Miele Ireland Ltd. 2024 Bianconi Avenue Citywest Business Campus Dublin 24 Tel. +3531 461 07 10 ITALY Miele Italia S.r.I. Strada di Circonvallazione, 27 39057 S. Michele-Appiano (BZ) Tel. +39 04 71/66 61 11 Telefax +39 04 71/66 63 50

JAPAN Miele Japan Corp. E Space Tower 11F 3-6 Maruyamacho Shibuya-ku Tokyo 150-0044 Japan Tel. +81(3)5784-0030 Telefax +81(3)5784-0035

KAZAKHSTAN Miele LLP Building 1B (office 602) Al-Farabi Pr. 13 050059 Almaty Tel. +7 727 3111141 Telefax +7 727 3111042

KOREA Miele Korea Limited Miele House 8 fl., 607-10 Yeoksam-dong Gangnam-gu Seoul 135-080 Selul 135-080 Telefax +82 2 3451 9353 Telefax +82 2 3451 9399

LATVIA Miele SIA Zaubes Str. 9A-38 1013 Riga Tel. +371 67889877 Telefax +371 67889879

LITHUANIA Miele Appliances UAB S. Zukausko g. 2/3-116 08240 Vilnius Tel. +370 52487529 Telefax +370 52487529

LUXEMBOURG Miele s.à r.l. 20, Rue Christophe Plantin 2339 Luxembourg Tel. +352/4 97 11-25 Telefax +352/4 97 11-39

MALAYSIA Miele Sdn Bhd Suite 12-2, Level 12 Menara Kencana Petroleum Solaris Dutamas No. 1, Jalan Dutamas 1 Kuala Lumpur 50480 Tel. +603 6205 3899 Telefax +603 6205 3998

MEXICO Miele S.A. de C.V. Av. Santa Fé 170 German Centre 0-4-2 Col. Lomas de Santa Fé C.P. 01210 México, D.F. Tel. +52/55 85 03 98 70 Telefax +52/55 85 03 98 74

NETHERLANDS Miele Nederland B.V. De Limiet 2 4131 NR Vianen Tel. +31 3 47/37 88 83 Telefax +31 3 47/37 84 29 NEW ZEALAND Miele New Zealand Ltd. Unit L, 10–20 Sylvia Park Road Mt. Wellington, 1060 Auckland Tel. +64 9573 1269 Telefax +64 9573 1268

NORWAY Miele AS Løxaveien 13 1351 Rud Tel. +47/67 17 31 00 Telefax +47/67 17 31 10

POLAND Miele Sp. z. o. o. ul. Gotarda 9 02-683 Warszawa Tel. +48 22/5 48 40 00 Telefax +48 22/5 48 40 10

PORTUGAL Miele Portuguesa, Lda. Av. do Forte, 5 2790-073 Carnaxide Tel. +351/21/42 48-100 Telefax +351/21/42 48-109

ROMANIA Miele Appliances SRL Intrarea Narciselor 8 Otopeni Jud. Ilfov Tel. +40 21 3520777 Telefax +40 21 3520776

RUSSIA 000 Miele CIS Leningradsky Prospekt, 31A, bld. 1 125284 Moscow Tel. +7 495 745-8992 Telefax +7 495 745-8680

SERBIA Miele d.o.o. Beograd Balkanska 2 Beograd – Stari Grad 11000 Tel. +381 11 2055060 Telefax +381 11 2055065

SINGAPORE Miele Pte. Ltd. 163 Penang Road #04-02/03 Winsland House II Singapore 238463 Tel. +65/67 35 11 91 Telefax +65/67 35 11 61

SLOVAKIA Miele s. r. o. Plynárenská 1 82109 Bratislava Tel. +421/2/58 10 31 11 Telefax +421/2/58 10 31 19

SLOVENIA Miele d.o.o. Brnőičeva ulica 41 g 1231 Ljubljana – Črnuče Tel. +386 1563 44-80 Telefax +386 1563 44-90

SOUTH AFRICA Miele (Pty) Ltd. 63 Peter Place Bryanston 2194 Tel. +27(0)11/5 48-19 00 Telefax +27(0)11/5 48-19 35 SPAIN Miele S.A.U. Carretera de Fuencarral, 20 28108 Alcobendas (Madrid) Tel. +34/91/6 23 20 00 Telefax +34/91/6 62 02 66

SWEDEN Miele AB Industrivägen 20 Box 1397 171 27 Solna Tel. +46 85 62 29-000 Telefax +46 85 62 29-209

SWITZERLAND Miele AG Limmatstr. 4 8957 Spreitenbach Tel. +4156 4 17 20 00 Telefax +4156 4 17-24 69

TURKEY Miele Elektrikli Aletler Dış, Tic. ve Paz. Ltd. Şti. Güvercin Sokak No. 10 34330 Levent-Istanbul Tel. +90/2 12/3 86-08 00 Telefax +90/2 12/3 25 84 49

UKRAINE Miele LLC Zhylyanskaya Str. 48, 50 A 01033 Kiev Tel. +38 044 4960300 Telefax +38 044 4942285

UNITED ARAB EMIRATES Miele Appliances Ltd. Gold & Diamond Park Sheikh Zayed Road Building No. 6, Office No. 219 Dubai Tel. +971 4 3418444 Telefax +971 4 3418852

USA Miele, Inc. 9 Independence Way Princeton, NJ 08540 Tel. 001-800/843 72 31 Telefax 001-609/419 42 41

OTHER COUNTRIES: Sales International Miele & Cie. KG Carl-Miele-Straße 29 33332 Gütersloh Tel. +49(0)52 41-89 15 07 Telefax +49(0)52 41-89 15 00